

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
8 September 2000 (08.09.2000)

PCT

(10) International Publication Number
WO 00/51860 A3(51) International Patent Classification⁷: **B60T 7/04**,
11/10, 1/06, F16D 55/228

(21) International Application Number: PCT/US00/05427

(22) International Filing Date: 2 March 2000 (02.03.2000)

(25) Filing Language: English


(26) Publication Language: English

(30) Priority Data:
60/122,405 2 March 1999 (02.03.1999) US(71) Applicants (for all designated States except US): **HAYES BRAKE, LLC** [US/US]; 5800 West Donges Bay Road, 104N, Mequon, WI 53092-4429 (US). **TEXTRON INC.** [US/US]; 40 Westminster Street, Providence, RI 02903 (US).(72) Inventor: **LANG, Joseph, A.** (deceased).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BROWN, Donald, D.** [US/US]; 515 Oakwood Drive, Thiensville, WI 53092 (US). **BUCKLEY, James, A.** [US/US]; 5111North Idlewild Avenue, Whitefish Bay, WI 53217 (US). **WALTERMAN, Scott, A.** [US/US]; 2748 North Hackett Avenue, Milwaukee, WI 53211 (US). **REESE, Terry, Lou** [US/US]; 5302 Henderson Road, Hephzibah, GA 30815 (US). **CRISCUOLO, James, M.** [US/US]; 1507 Center Star Road, Columbia, TN 38401 (US).(74) Agents: **NEWHOLM, Timothy, E.** et al.; Boyle Fredrickson Ziolkowski S.C., 250 Plaza, Suite 1030, 250 East Wisconsin Avenue, Milwaukee, WI 53202 (US).(81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **BRAKE SYSTEM HAVING HYDRAULIC ACCUMULATOR AND/OR COMBINED SERVICE BRAKE AND PARK AND HOLD BRAKE**

(57) Abstract: A hydraulic brake system (50) for a vehicle such as a golf car or the like uses the same brakes (52) and same brake pedal (80) for both service braking and park and hold braking. The brakes (52) are selectively engaged, locked in their engaged position, and released using an integrated control assembly including a brake pedal (80), an accelerator pedal (82), and a brake pedal locking mechanism (84). The brake pedal locking mechanism (84) is configured to automatically latch the brake pedal (80) in a locked position thereof and to automatically unlatch the brake pedal (80) from its locked position upon either subsequent movement of the brake pedal (80) into an overtravel position or subsequent actuation of the accelerator pedal (82). In addition, a hydraulic accumulator (62) stores part of the energy generated upon brake pedal depression and consequent manual actuation of a master cylinder (60) of the system to maintain the brakes (52) in their fully engaged state when the brake pedal (80) is latched. The stored energy can also be used to help return an applied brake pedal (80) to its released position, in which case return fluid flow to the master cylinder (60) is damped to avoid undesirable severe kickback of the brake pedal. The accumulator (62) preferably comprises a modular spring and retainer assembly that can be preassembled separately from the remainder of the system and subsequently mounted on the system as a unit.

WO 00/51860 A3